

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

1 1. (currently amended) A camera control apparatus comprising:

2 an image data receiving section for receiving from an  
3 image transmitter image data captured by one of a  
4 plurality of cameras;

5 an image data playback section for displaying the  
6 received images on a screen;

7 a camera control area display section for displaying  
8 camera symbols which correspond to information  
9 representing the locations of the cameras and the  
10 directions in which the cameras are oriented as a  
11 control region for controlling the plurality of  
12 cameras connected to the image transmitter;

13 a command load section for loading the coordinates of a  
14 location in the control region designated by an  
15 operator;

16 a camera-to-be-operated determination section for  
17 determining a camera optimal for shooting the  
18 designated location from the plurality of cameras;

19 a control command conversion section for converting  
20 information about the coordinates loaded by the  
21 command load section into a control command signal  
22 capable of being used for controlling the plurality  
23 of cameras; and

24 a control command transmission section for transmitting  
25 the converted control command signal to the image  
26 transmitter, wherein

27        said camera-to-be-operated determination section  
28                determines[[a]] which one of said plurality of  
29                cameras is to be panned on the basis of an angle  
30                between an imaginary line connecting the center of  
31                the camera symbol with the designated location and  
32                an imaginary line connecting the center of the  
33                camera symbol with the direction in which the camera  
34                is currently oriented.

1    2. (canceled)

1    3. (previously presented) The camera control apparatus as  
2    defined in claim 1, further comprising an employable camera  
3    survey section which stores information about the positions of  
4    obstructions existing in the line of sight to be shot by the  
5    plurality of cameras and which eliminates a camera undesirable  
6    for shooting the designated location from candidates  
7    considered by the camera-to-be-operated determination section.

1    4. (previously presented) The camera control apparatus as  
2    defined in claim 3, wherein, in the event of presence of an  
3    obstruction of the view between the area to be shot and one or  
4    more of the cameras in the area where the cameras are  
5    disposed, the obstruction is displayed.

1    5. (previously presented) A camera control apparatus  
2    comprising:  
3        an image data receiving section for receiving image data  
4        captured by cameras from an image transmitter;

5 an image data playback section for displaying the  
6 received images on a screen;  
7 a camera control area display section for displaying  
8 camera symbols which correspond to information  
9 representing the locations of the cameras and the  
10 directions in which the cameras are oriented as a  
11 control region for controlling the cameras connected  
12 to the image transmitter;  
13 a command load section for loading the coordinates of a  
14 location in the control region designated by an  
15 operator;  
16 a camera-to-be-operated determination section for  
17 determining a camera optimal for shooting the  
18 designated location;  
19 a control command conversion section for converting  
20 information about the coordinates loaded by the  
21 command load section into a control command signal  
22 capable of being used for controlling the cameras;  
23 a control command transmission section for transmitting  
24 the converted control command signal to the image  
25 transmitter;  
26 an angular-shift-time calculation section for calculating  
27 the time required for the camera to pan toward the  
28 designated location;  
29 a focus storage section for grasping the focus of a  
30 plurality of cameras; and  
31 a focus-shift-time calculation section for calculating  
32 the time required for the camera to attain a focus  
33 on the designated location,

34 wherein the camera-to-be-operated determination section  
35 determines a camera which can shoot the designated  
36 location in the minimum time as a camera to be  
37 operated, on the basis of the time required for the  
38 camera to pan toward the designated location, as  
39 well as the time required for the camera to attain a  
40 focus on the designated location.

1 6. (original) The camera control apparatus as defined in claim  
2 5, wherein there are displayed not only the direction in which  
3 the camera is oriented but also the focusing state of the  
4 camera.

1 7. (previously presented) A camera control apparatus  
2 comprising:  
3 an image data receiving section for receiving image data  
4 captured by cameras from an image transmitter;  
5 an image data playback section for displaying the  
6 received images on a screen;  
7 a camera control area display section for displaying  
8 camera symbols which correspond to information  
9 representing the locations of the cameras and the  
10 directions in which the cameras are oriented as a  
11 control region for controlling the cameras connected  
12 to the image transmitter;  
13 a command load section for loading the coordinates of a  
14 location in the control region designated by an  
15 operator;

16           a camera-to-be-operated determination section for  
17           determining a camera optimal for shooting the  
18           designated location;  
19       a control command conversion section for converting  
20           information about the coordinates loaded by the  
21           command load section into a control command signal  
22           capable of being used for controlling the cameras;  
23       a control command transmission section for transmitting  
24           the converted control command signal to the image  
25           transmitter;  
26       a view-point direction survey section for storing the  
27           direction in which the operator desires to shoot the  
28           designated location,  
29       wherein the camera-to-be-operated determination section  
30           determines a camera to be operated, from information  
31           as to whether or not an image can be shot in the  
32           direction designated by the view-point survey  
33           section, as well as from the angle between the  
34       current shooting direction of the camera and the  
35           direction of an imaginary line connecting the  
36           designated location with the center of the camera  
37           symbol.

1   8. (original) The camera control apparatus as defined in claim  
2   7, wherein there is displayed information about the direction  
3   in which the operator desires to shoot.

1   9. (previously presented) A camera control apparatus  
2   comprising:

3       an image data receiving section for receiving image data  
4             captured by cameras from an image transmitter;  
5       an image data playback section for displaying the  
6             received images on a screen;  
7       a camera control area display section for displaying  
8             camera symbols which correspond to information  
9             representing the locations of the cameras and the  
10            directions in which the cameras are oriented as a  
11            control region for controlling the cameras connected  
12            to the image transmitter;  
13       a command load section for loading the coordinates of a  
14            location in the control region designated by an  
15            operator;  
16       a camera-to-be-operated determination section for  
17            determining a camera optimal for shooting the  
18            designated location;  
19       a control command conversion section for converting  
20            information about the coordinates loaded by the  
21            command load section into a control command signal  
22            capable of being used for controlling the cameras;  
23       a control command transmission section for transmitting  
24            the converted control command signal to the image  
25            transmitter;  
26       an angular-shift-time calculation section for calculating  
27            the time required for the camera to pan toward the  
28            designated location;  
29       a zoom storage section for grasping the degree of zoom of  
30            a plurality of cameras;

31 a zoom-shift time calculation section for calculating the  
32 time required for a camera to zoom in order to  
33 display an image of the designated range; and  
34 a zoom range display section for displaying, in the  
35 camera control region, a range to be zoomed,  
36 wherein the camera-to-be-operated determination section  
37 determines a camera to be operated, from the time  
38 required for the camera to pan toward the designated  
39 location after the operator has designated a desired  
40 range in the control region and the time required  
41 for the camera to zoom in or out for attaining focus  
42 on the designated range.

1 10. (original) The camera control apparatus as defined in  
2 claim 1, wherein an image captured by the camera selected by  
3 the camera-to-be-operated determination section is displayed  
4 greater than images captured by other cameras.

1 11. (previously presented) The camera control method as  
2 defined in claim 13, wherein, when a camera most optimal for  
3 shooting the designated location is selected, an image  
4 captured by the thus-selected camera is displayed greater than  
5 images captured by other cameras.

1 12. (canceled).

1 13. (previously presented) A camera control method comprising  
2 steps of:

3 displaying images captured by a plurality of cameras, a  
4 map relating to a location whose image is captured  
5 by the plurality of cameras, camera symbols  
6 representing the locations of the cameras in the  
7 map, and directions in which the cameras are  
8 oriented;

9 selecting a camera optimal for shooting a location  
10 designated by an operator;

11 and

12 controlling the selected camera such that the camera is  
13 panned toward the designated location, wherein, from  
14 among the plurality of cameras, there is selected a  
15 camera involving a minimum angle between the  
16 direction in which the camera is currently oriented  
17 and an imaginary line connecting the center of the  
18 camera symbol with the designated location.

1 14. (canceled).

1 15. (original) The camera control method as defined in claim  
2 13, wherein the camera which is blocked by an impediment and  
3 cannot shoot the designated location is eliminated from  
4 candidates for selection of a camera to be operated.

1 16. (original) The camera control method as defined in claim  
2 15, wherein, in the event of presence of an impediment in the  
3 area where the cameras are disposed, the impediment is  
4 displayed.



1 17. (previously presented) A camera control method comprising  
2 the steps of:

3 displaying images captured by a plurality of cameras, a  
4 map relating to a location whose image is captured  
5 by the plurality of cameras, camera symbols  
6 representing the locations of the cameras in the  
7 map, and directions in which the cameras are  
8 oriented;

9 selecting a camera optimal for shooting a location  
10 designated by an operator; and

11 controlling the selected camera such that the camera is  
12 panned toward the designated location,

13 wherein, from among the plurality of cameras, a camera  
14 which can shoot the designated location within the  
15 minimum period of time is selected on the basis of  
16 the time required for the camera to pan toward the  
17 designated location from the direction in which the  
18 camera is currently oriented and the time required  
19 for the camera to zoom into the designated location,  
20 and the selected camera is panned toward the  
21 designated location and attains focus on the  
22 designated location.

1 18. (original) The camera control method as defined in claim  
2 17, wherein there are displayed not only the direction in  
3 which the camera is oriented but also the focusing state of  
4 the camera.

1 19. (original) The camera control method as defined in claim  
2 13, wherein cameras incapable of shooting an image from a  
3 direction desired by the operator are eliminated from  
4 candidates camera-to-be-operated.

1 20. (original) The camera control method as defined in claim  
2 19, wherein there is displayed information about the direction  
3 in which the operator desires to shoot.

1 21. (previously presented) A camera control method comprising  
2 the steps of:

3 displaying images captured by a plurality of cameras, a  
4 map relating to a location whose image is captured  
5 by the plurality of cameras, camera symbols  
6 representing the locations of the cameras in the  
7 map, and directions in which the cameras are  
8 oriented;

9 selecting a camera optimal for shooting a location  
10 designated by an operator; and

11 controlling the selected camera such that the camera is  
12 panned toward the designated location,

13 wherein, from among the plurality of cameras, there is

14 selected a camera which can shoot the designated  
15 range within the minimum period of time, on the  
16 basis of the time required for the camera to pan  
17 toward a designated range from the direction in  
18 which the camera is currently oriented after the  
19 camera has received an instruction for designating a  
20 desired range from the operator, and the time

21               required for the camera to attain focus on the  
22               designated range from the range on which the camera  
23               is currently focused, and the selected camera is  
24               panned toward the designated location, to thereby  
25               attain focus on the designated range.

1   22. (canceled).